

Addressable detectors

DOD-220A



Addressable optical smoke detector, with dirt compensation and algorithm verification. Led status indicator anti-theft system and output for remote pilot indicator PAD-10 or buzzer BUD-200. White color. Non polarity installation. Requires connection base Z-200 or Z-200-H. CPR certificate EN54-7. Dimensions: 100 x 40 mm.

DOTD-230A



Addressable optical & heat detector, with dirt compensation and algorithm verification. Led status indicator anti-theft system and output for remote pilot indicator PAD-10 or buzzer BUD-200. White color. Non polarity installation. Requires connection base Z-200 or Z-200-H. CPR certificates EN54-5 and EN54-7. Dimensions: 100 x 40 mm.

DTD-210A



Addressable heat (58°C fixed temperature and thermal rate of rise) detector, with algorithm verification. Led status indicator and output for remote pilot or buzzer, anti-theft system. White color. Allows installation without polarity. Requires base Z-200 or Z-200-H. CPR certificate EN54-5. Dimensions: 100 x 40 mm.

DTD-215A



Addressable high temperature detector (fixed at 78°C), with algorithm verification. Led status indicator and output for remote pilot or buzzer, anti-theft system. White color. Allows installation without polarity. Requires connection base Z-200 or Z-200-H. CPR certificate EN54-5. Dimensions: 100 x 40 mm.

Addressable detectors with built-in isolator

D0D-220A-I



Addressable optical smoke detector with built-in isolator, with dirt compensation and algorithm verification. Led status indicator anti-theft system and output for remote pilot indicator PAD-10 or buzzer BUD-200. White color. Requires connection base Z-200 or Z-200-H. CPR certificate EN54-7 and EN54-17. Dimensions: 100 x 40 mm.

DOTD-230A-I



Addressable optical & heat detector with built-in isolator, with dirt compensation and algorithm verification. Led status indicator anti-theft system and output for remote pilot indicator PAD-10 or buzzer BUD-200. White color. Requires connection base Z-200 or Z-200-H. CPR certificates EN54-5, EN54-7 and EN54-17. Dimensions: 100 x 40 mm.

DTD-210A-I



Addressable heat (58 °C fixed temperature and thermal rate of rise) detector with built-in isolator, with algorithm verification. Led status indicator and output for remote pilot or buzzer, anti-theft system. White color. Requires base Z-200 or Z-200-H. CPR certificate EN54-5 and EN54-17. Dimensions: 100 x 40 mm.

DTD-215A-I



Addressable high temperature detector (fixed at 78°C) with built-in isolator, with algorithm verification. Led status indicator and output for remote pilot or buzzer, anti-theft system. White color. Requires connection base Z-200 or Z-200-H. CPR certificate EN54-5 and EN54-17. Dimensions: 100 x 40 mm

Addressable detectors (black)

DOD-220A-B



Addressable optical smoke detector, with dirt compensation and algorithm verification. Led status indicator anti-theft system and output for remote pilot indicator PAD-10 or buzzer BUD-200. Black color. Non polarity installation. Requires connection base Z-200 or Z-200-H. CPR certificate EN54-7. Dimensions: 100 x 40 mm.

DOTD-230A-B



Addressable optical & heat detector, with dirt compensation and algorithm verification. Led status indicator anti-theft system and output for remote pilot indicator PAD-10 or buzzer BUD-200. Black color. Non polarity installation. Requires connection base Z-200 or Z-200-H. CPR certificates EN54-5 and EN54-7. Dimensions: 100 x 40 mm.

DTD-210A-B



Addressable heat (58°C fixed temperature and thermal rate of rise) detector, with algorithm verification. Led status indicator and output for remote pilot or buzzer, anti-theft system. Black color. Allows installation without polarity. Requires base Z-200 or Z-200-H. CPR certificate EN54-5. Dimensions: 100 x 40 mm.

DTD-215A-B



Addressable high temperature detector (fixed at 78°C), with algorithm verification. Led status indicator and output for remote pilot or buzzer, anti-theft system. Black color. Allows installation without polarity. Requires connection base Z-200 or Z-200-H. CPR certificate EN54-5. Dimensions: 100 x 40 mm.