

# Addressable sounders and beacons

## MAD-461-I



**Addressable loop sounder with isolator.** Low power consumption, acoustic power 87.5 dB. It takes just one address in the loop. Color red. For indoor use. IP21. CPR certificate EN54-3 and EN54-17. Dimensions: 65x90 mm.

## MAD-463-I



**Addressable loop sounder with beacon and isolator.** Low power consumption, acoustic power 87.5 dB. It takes just one address in the loop. Color red. For indoor use. IP21. CPR certificate EN54-3 and EN54-17. Dimensions: 65x90 mm.

## MAD-464-I



**Addressable loop sounder with built-in isolator.** Low power consumption. 32 tones and 3 configurable volumes (Low, Medium, High). Acoustic power from 78.3 dBA to 104.6 dBA depending on the selected tone. It takes just one address in the loop. Red color. IP65. Deep base. CPR certificate EN54-3 and EN54-17. Dimensions: 100 x 75 mm

## MAD-465-I



**Addressable loop sounder with beacon and built-in isolator.** Low power consumption. 32 tones and 3 configurable volumes (Low, Medium, High). Acoustic power 76 dBA to 117 dBA depending on the selected tone. It takes just one address in the loop. Red color. From IP65. Deep base. CPR certificate EN54-3 and EN54-17. Dimensions: 100 x 75 mm

## MAD-472



**Addressable loop connection base with sounder.** 200A detector compatible. CPR Certified EN54-3. Acoustic power: 80dB. Indoor use. IP30. Dimensions: 150 x 100 mm.

## MAD-473



**Addressable loop connection base with sounder and beacon.** 200A detector compatible. CPR Certified EN54-3. Acoustic power: 80dB. Indoor use. IP30. Dimensions: 150 x 100 mm.

## MAD-467-IC



**Addressable loop sounder with white beacon for ceiling installation, and built-in isolator.** Beacon cover C-2.4-7. Low power consumption. 32 tones and 3 configurable volumes (Low, Medium, High). Acoustic power 76 dBA to 117 dBA depending on the selected tone. It takes just one address in the loop. Red color. Indoor use. IP21C. Deep base. CPR Certificate EN54-3, EN54-17 and EN54-23. Dimensions: 100 x 75 mm

### MAD-467-IW



**Addressable loop sounder with white beacon for wall installation, and built-in isolator.** Beacon cover W-2.4-8. Low power consumption. 32 tones and 3 configurable volumes (Low, Medium, High). Acoustic power 76 dBA to 117 dBA depending on the selected tone. It takes just one address in the loop. Red color. Indoor use. IP21C. Deep base. CPR Certificate EN54-3, EN54-17 and EN54-23. Dimensions: 100 x 75 mm

### MAD-469-IC



**Addressable beacon of white color with red base for ceiling installation, with built-in isolator.** Beacon cover C-2.4-7. IP33C. For direct connection to the loop. Low power consumption. Indoor use. CPR Certificate EN54-23 and EN54-17.

### MAD-469-IW



**Addressable beacon of white color with red base for wall installation, with built-in isolator.** Beacon cover W-2,4-8. IP33C. For direct connection to the loop. Low power consumption. Indoor use. CPR Certificate EN54-23 and EN54-17.