

Conventional manual call points

PCD-100



Conventional manual call point, with test key, for surface installation. Suitable for indoor. Red color. Includes resistance of 100 Ohm.-2W. Dimensions: 98 x 98 x 48 mm. CPR certificate EN54-11

TBD-450



Protective plastic cover, for indoors PCD-100, MAD-450 or MAD-450-I manual call points.

SMD-450



Call point recessing bezel for indoor use, PCD-100, MAD-450 or MAD-450-I. Red color.

PCD-100WP



Conventional manual call point IP67, with test key, for surface installation. Suitable for outdoor. Red color. No resistance of 100 Ohm included.-2W. Dimensions: 119 x 128 x 62 mm. CPR certificate EN54-11.

RP-GS1



Conventional manual call point for evacuation and emergencies. Green color, surface installation. Suitable for Indoors. Dimensions: 98 x 98 x 48 mm.

TBD-450-IW



Plastic protective cover for RP-GS1, PCD-100WP and MAD-450-IW outdoor manual call points

STI-13110ESP



Outdoor protector for PAD-100 or MAD-450 manual call points. Made of hard and transparent polycarbonate. Recommended to avoid vandalism, misuse, situations of involuntary activation of the call point, dust, water and weather indemics. Includes a seal that seals the unit preventing the entry of dust, dirt and water. IP54.
Dimensions: 101 x 126 x18 mm