

Conventional control panel accessories

TRD-100



Expansion card of 4 free voltage relay outputs for conventional CCD-100 control panels. Maximum load: 10A at 30Vdc. Maximum 3 cards per panel. Programmable via SWD-100 software.

TSD-100



4 supervised sounder outputs card, for conventional CCD-100 control panels, allowing four independent sounder outputs. Maximum load: 500 mA per output. Maximum 3 cards per panel. Programmable via SWD-100 software.

TMD-100



RS485 communication card for integration to a network using the Modbus protocol, for conventional CCD-100 panels. Allows remote control of the main functions of the fire panel and integrate it with third parties.

TPLD-100



Addressable loop gateway card for conventional CCD-100 and CCD-103 panels range. Allows alarms and faults communication from the conventional control panel to the addressable loop to a CAD-150 control panel range.

TED-151-WS



TCP / IP communication card with embedded Webserver for conventional CCD-100 panel range or addressable CAD- 150 control panels. Allows remote maintenance and remote control the panel in which it is built in. Automatic sending of emails.

TCD-106-C



CMS (Central Monitoring Station) IP / GPRS communication card, Contact ID protocol to transmit the alarm and faults. Compatible with the conventional CCD-100 fire panel range. RS485 connection between the fire panel and the card. Power supply to 24V.
